WIND SENSORS "ECONOMY"

Wind direction and Wind speed

manual





Good orientation...

is provided by these wind measuring sensors proven a thousand times.

The dimensionally stable measuring parts, the robust all-metal housing, good starting values and linearity amount to a very good price-performance ratio.

Best prerequisites for world-wide

good response sensitivity

applications in any location.

- high accuracy across large tempe rature range
- 3 output signals
- simplest installation by means of plug-in connection and fixing with one screw
- with integrated heating absolutely winter-fit

wind power plants • building services • wind warning devices for cranes • industrial applications • in all climatic zones

Standard Line

Id-No.:

Measuring elements: Measuring range/ Accuracy: Resolution/ Starting value: Outputs:

Dimensions:

Measuring principle: Range of application: Supply voltage: Housing: Weight: Included in delivery:

Accessories:

32.14565.060 000 32.14565.060 020

Wind Sensors ECONOMY

(14565 24V) Wind direction 00.14565.200 304

blade wind vane • dimensionally stable $0...360^{\circ} \bullet \pm 3.6^{\circ}$ $2.5^{\circ} \bullet \langle 0.7 \text{ m/s}$ $0...20 \text{ mA} \bullet \text{max. load 500 } \Omega$ $4...20 \text{ mA} \bullet \text{max. load 500 } \Omega$ $3 \text{ x 0...10 V}_{\text{DC}}$ wind vane L 195 mm \cdot H 260 mm

(14575 24V) Wind speed 00.14575.200 004

3-armed cup rotor \bullet fail-safe 0.7...35 m/s \bullet \pm 2% FS 0.1 m/s \bullet < 0.7 m/s 0...20 mA = 0...35 m/s \bullet max. load 500 Ω 4...20 mA = 0...35 m/s \bullet max. load 500 Ω 0...700 Hz = 0...35 m/s \bullet max. load 500 Ω cup rotor \emptyset 95 mm \cdot H 155 mm

opto-electronical

temperatures -3o...+7o°C heated • wind speed o...6o m/s 1o...3o V_{DC} for internal transducer • heating 24 V_{DC} / 600 mA · electr. controlled aluminium · anodized · IP 53 · Ø 74 mm · RAL 9002 (grey-white) · for mounting pipe Ø 50 mm approx. 0.4 kg

1 plug \cdot 12-pole \cdot when a cable is ordered, the plug is mounted to that

(14565 U60) Cable · 12 m · with 12-pole plug · ready-made **(14565 U60b)** Cable · 15 m · with 12-pole plug · ready-made **Indicator units** e. g. (1476 Q144N) · (1477 Q144)

Traverses/ Masts and Power supply units see chapter "Periphery"





